

Caratteristiche generali



Temperature range	Adjustable +15°C / +30°C
Factory setpoint Increment	+22°C 0,1°C
Ambient working class Climatic class	From +16°C to +38°C N-ST
Nominal capacity	140 lt (4,94 cu ft)
Gross capacity Net capacity	153 lt (5,40 cu ft) 128 lt (4,52 cu ft)
External dimensions (WxDxH)	52x63,5x83 cm
Internal dimensions (WxDxH)	44x51,6x56 cm
Net weight without any internal fittings	49 kg



Package dimensions Weight	Cardboard on pallet 55x69x100 cm weight 57,5 kg Wooden crate on pallet 60x77x103 cm weight 67,5 kg
Structure	Monocoque type, made of plasticized, non-toxic white steel interior/exterior, coated with a special antibacterial-type film, or in inner 18/10 Aisi 304 stainless steel. Rounded corners and tray-type inner bottom.
Insulation type	High-density (43 kg/m ³), in-walls injected PUF, without any CFC, water-foam based.
Insulation thickness	40 mm
Feet	No.4 adjustable small feet
Door	No.1 solid door with ergonomic handle, self-closing thanks to the spring hinge and 90°stop position.
Lightning	Full LED, all length of inner chamber, automatic switching on at door opening.



Internal fittings	Customizable and height adjustable, it can mix independently: <ul style="list-style-type: none"> • wire shelves supported by adjustable clips (dim.cm.40x49) • fully extractible drawers made of aluminium, with dividers (WxDxH): cm 10x45x7,5 (nr 3 compartments) • fully extractible drawers made of aluminium, without dividers (WxDxH): cm 33x45x7,5
Suggested internal fittings	No. 2 wire shelves

Refrigeration system

Refrigeration	Professional, ventilated, forced, hermetic compressor type
Defrost	Automatic, adaptive, including condensate water vaporisation
Refrigerant	Natural R290
GWP ODP	3 0

Disclaimer:
Images are purely indicative. The features and the accessories of the products may differ according to model and application.

Electronic controller



Controller	Controller ECT-F control®
Type of controller	Electronic controller, back-lit alphanumeric LCD display and resolution 0,1°C
Power switch	Integrated in user's interface
Security features	Settable user password
Alarm system	Visual and acoustic for temperature alarms and failures such as: <ul style="list-style-type: none">• Open door• High temperature• High temperature caused by power failure.• Low temperature• Power failure (when the energy returns, only in event of High Temperature)• Clogged condenser• Any functional failure/faulty parts
Data and event recordings	Last 12 events available on the display
Settable temperature alarm limits	Yes, through parameter adjustment
Control sensors	NTC type probes

Electrical and functional data

Standard power supply	230V / 1ph / 50Hz
Standard plug type	Schuko type "G"
Compressor protection	Overload Protector included
Power absorption/current	kW 0,14 (Amp 0,9)
Inrush current	Amp 2,5
Noise level	<40 dBA
Heat emission according to EN 12900	W 20
Energy consumption at 20°C ambient	0,6 kWh/24h

Conformity

Directives and regulations	Directive 2006/42/EC (Machine directive) Directive 2011/65/EC (ROHS II) Directive 2015/863/ EC (ROHS III) Directive 2012/19/EC (RAEE) Directive 2014/30/EC (EMC) Directive 2014/35/EC (LVD) Regulation (EU) 517-2014 (F-gas) Regulation (EU) 1907-2006_REACH
Available certificate	CE
Application environment	Non-flammable, non-explosive, non-corrosive, with adequate air exchange

FIOCCHETTI SCIENTIFIC S.R.L.

Headquarter: Via Panagulis, 48 - 42045 Luzzara (RE) Italy
VAT No. IT00934960352

Phone +39 0522 976232 - Fax +39 0522 976028

www.fiocchetti.com - Email: info@fiocchetti.it - Pec: fiocchetti@pec.it

Accessories available on request

Glass door

Lock with key

DMLP Digital Monitor®

Alarm and temperature recording system completely independent from the ECT-F control® controller, equipped with buffer battery and featuring an additional backlit, alphanumeric LCD display.

DMLP Digital Monitor provides:

Temperature and alarms data recording on extractible SD card covering the last 5 years, with one minute sampling frequency.

Back-up buffer battery granting alarms and recording during power cut. The life of the battery is approximately 12 hours during power failures.

Pre-set for alarms remoting (dry contact)

The SD can be inserted in any pc using a card-reader and includes a freely supplied software, Capture, allowing to download, save and print any data.

Information can be arranged as a graph or tabular forms, both fully customizable.

DMLP Printer

ECT-F PLUS controller

Evolution of ECT-F control® controller, including following additional features:

Backup batteries for power failure alarm, up to 48 Hrs

Min and Max temperature log, manually resettable

High temperature alarm during power failure

Refrigerator temperature visible even during power failure

Alarm contact available on control board, remotable

Additional programmable relays output available

Please refer to model TER 140 ECT-F PLUS

Additional wire shelf kit

Extractible drawer on telescopic slides

Extractible drawer without inner dividers on telescopic slides

Plexiglas front panel for extractible drawer

Castors kit with brakes

One-way small castors

Inner socket (no.1)

35mm access port with stopper (no.1)

Port hole mm 15 (no.1)

No.1 humidity sensor

No.1 PT100 sensor with free contacts

Non-standard plug and cable

Power 220V/60Hz

Power 115V/60Hz

Mains voltage stabilizer

Wooden crate package

FIOCCHETTI SCIENTIFIC S.R.L.

Headquarter: Via Panagulis, 48 - 42045 Luzzara (RE) Italy
VAT No. IT00934960352

Phone +39 0522 976232 - Fax +39 0522 976028

www.fiocchetti.com - Email: info@fiocchetti.it - Pec: fiocchetti@pec.it