

Multi Bio RS-24, Programmable rotator


DESCRIPTION

Programmable Rotator **Multi Bio RS-24** performs several motion types in one module. Microprocessor control allows performing not only Vertical rotation (1) of the platform, but also Reciprocal rotation (2) as well as Vibration (3). These three motion types can be performed separately, pairwise and in cycles, periodically repeating the sequence of three motion types. Multi-Rotation option of Biosan instruments substantially expands possibilities and enhances efficiency of sample preparation for the examined materials and allows adjusting the mixing procedure according to the individual tasks.

Programmable Rotator can be used for variety of applications in modern life science laboratories: for hybridization reactions, cell growing, soft extraction and homogenisation of biological components in solutions, as well as for reactions of binding and washing of magnetic particles.

During the stop mode the platform does not perform extra turnover and stops in a horizontal plane. Additionally there is a possibility of setting the plane with respect to which platform oscillates vertically or horizontally.

Programmable Rotator can be used in cold rooms or incubators, operating at ambient temperature range +4°C to +40°C. Low voltage external power supply (12 V) provides electrical safety in humid environment.



PRS — series platforms are equipped with universal rubber clamps for different size tube fixation;
PRSC — series platforms have metal clamps able to hold heavier solutions (e.g. soil, sand).



CAT. NUMBER

| Including PRS-26 platform | Including PRS-26 platform |
|---------------------------|--|
| BS-010117-AAG | 230VAC 50/60Hz Euro plug |
| BS-010117-AAK | 100-240VAC 50/60Hz Multi plug (EU, UK, AU, US) |
| BS-010117-MK | IQ OQ document |
| BS-010117-NK | PQ document |

SPECIFICATIONS

| | |
|---|--|
| Digital time setting | 1 min–24 hrs / non–stop (increment 1 min) |
| Timer sound signal | + |
| Vertical rotation speed control range | 1–100 rpm (increment 1 rpm) |
| Vertical rotation movement | overhead, 360° |
| Vertical rotation time setting range | 0 - 250 sec |
| Maximum continuous operation time | 168 h |
| Reciprocal rotation speed control range | 1–100 rpm (increment 1 rpm) |
| Reciprocal rotation tilt angle range | 1° - 90° (increment 1°) |
| Reciprocal rotation time setting range | 0 - 250 sec |
| Vibro rotation tilt angle range | 0° - 5° (increment 1°) |
| Vibro rotation Pause / Vibro time setting range | 0 - 5 sec |
| Maximum load | 0.5 kg |
| Overall dimensions (W×D×H) | 365×195×155 mm |
| Weight | 1.7 kg |
| Input current/power consumption | 12 V, 660 mA / 8 W |
| External power supply | Input AC 100–240 V; 50/60 Hz; Output DC 12 V |

ACCESSORIES



PRS-26
BS-010117-GK
platform

Can accommodate 26 tubes 10–16 mm diameter (1.5–15 ml).



PRS-5/12
BS-010117-HK
platform

5 tubes 20–30 mm diameter (50 ml tubes) and 12 tubes 10–16 mm diameter (1.5–15 ml tubes).



PRS-10
BS-010117-IK
platform

10 tubes 20–30 mm diameter (up to 50 ml tubes).




PRSC-22
BS-010117-LK
platform

Can accommodate 22 tubes 16 mm diameter (15 ml).



PRSC-10
BS-010117-JK
platform

10 tubes 25–30 mm diameter (50 ml tubes).




M-8/50
BS-010117-PK
platform

Roller platform, 8 tubes 25–30 mm diameter (50 ml tubes).
Application: hybridization reactions.




PRS-1DP
BS-010149-DK
platform

Platform for microplates and racks for tall tubes 0.5 and 1 ml (e.g. Thermo 3741MTX, 3742MTX, 3744MTX).



RP-8/15
BS-010117-DK
roller platform

Roller platform, 8 tubes (15 ml). 5° incline for enhanced mixing homogeneity.



RP-8/50
BS-010117-KK
roller platform

Roller platform, 8 tubes (50 ml). 5° incline for enhanced mixing homogeneity.