

PST-100HL, Plate Shaker-Thermostat

DESCRIPTION

Plate Thermo-Shakers are designed for shaking and thermostating 2 standard 96-well microplates.

A multisystem principle, used in design of the Thermo-Shaker, allows operating it as 3 independent devices:

- Incubator;
- Microplate shaker;
- Thermo-Shaker.

A distinctive feature of Biosan Plate Thermo-Shakers is the patented by the company **Two-Side Microplates Heating**, which allows to achieve full correspondence of the set and actual temperature in the microplate wells.

Thermo-shaker **PST-100HL** with the ability to stabilize the temperature up to 100 ° C is specially designed for the hybridization reactions.

Plate Shaker-Thermostat provides:

- Soft or intensive sample shaking
- Rotation speed regulation, stabilization and indication
- Even rotation amplitude throughout the Thermo-Shaker platform
- Required operation time setting and indication
- Automatic stopping of the platform movement after expiration of the set time
- Setting and indication of the required temperature on the platform

Application fields:

- Cytochemistry — for in situ reactions
- Immunochemistry — for immunofluorescent reactions
- Biochemistry — for enzyme and protein analysis
- Molecular biology — for micro array analysis



CAT. NUMBER

BS-010142-AAI	230VAC 50/60Hz Euro plug
BS-010142-AAQ	230VAC 50/60Hz UK plug
BS-010142-AA4	230VAC 50/60Hz AU plug
BS-010142-AAJ	100VAC 50/60Hz US plug, 120VAC 60Hz US plug
BS-010142-AK	IQ OQ document
BS-010142-BK	PQ document

SPECIFICATIONS

Temperature setting range	+25°C ... +100°C
Temperature control range	+5°C above ambient ... +100°C
Temperature setting resolution	0.1°C
Temperature stability	±0.1°C
Temperature uniformity at +37°C	±0.2°C
Temperature calibration coefficient range	0.936...1.063 (± 0.063)
Heating	Patented two-side microplate heating
Speed control range	250–1200 rpm (increment 10 rpm)
Digital time setting	1 min–96 hrs / non-stop (increment 1 min)
Timer sound signal	+
Orbit	2 mm
Display	LCD, 16 x 2 signs
Maximum continuous operation time	168 h
Max. height of microtest plate	18 mm
Number of microtest plates	2
Platform dimensions (w x d)	250 x 150 mm
Overall dimensions (W×D×H)	270 x 260 x 125 mm
Weight	5.9 kg
Input current/power consumption	12 V, 5 A / 60 W
External power supply	Input AC 100–240 V; 50/60 Hz; Output DC 12 V