

Laboratory Essential

Freezer

39L Laboratory Essential Countertop Freezer with Solid Door

Product code LSFSF39DC-UK

SKU code 444411346







Key features

- √ Temperature range of -18°C to -25°C
- ✓ Air temperature probe

- ✓ Audible and visual temperature alarms
- ✓ Factory fitted 16mm porthole for secondary temperature monitoring probes



External Digital Controller

Temperatures are easy to read on the clear digital display. Read, record, and reset simply with the touch of a button.



Fitted Lock

Integrated lock, comes with two keys for added security and access control, to keep contents safe.



Spark-free

We have removed items such as fans and lights so nothing in the interior of the appliance has a risk of igniting flammable liquids



Anti-Microbial Handle

Our handles have an anti-microbial powder coating which inhibits the growth of microbes to help prevent cross contamination.



SKU Code Product Code	444411346 LSFSF39DC-UK
roduct code iross Capacity (litres)	39L E2F2F39DC-0K
let Capacity (litres)	35L
Init External Width (mm)	475mm
Init External Depth (mm)	445mm
Init External Height (mm)	565mm
roduct Weight (kg)	19kg
racked Width (mm)	505mm
Packed Depth (mm)	510mm
Packed Height (mm)	585mm
Packed Weight (kg)	21.1kg
Country of Origin	UK
	370mm x 345mm x 404mm
nternal Dimensions (mm) (WxDxH)	
emperature Range	-18°C to -25°C
Colour	White/Green
external Finish	Painted Steel
nternal Finish	HIPS*
ype of plastic	SRL800 (HIPS/ABS mix)
Door Finish	Painted Steel / Solid
oor Type	Solid
Door Style	Hinged, Reversible
Door Liner	Flat
lumber of Door Trays	N/A
lumber of Door Tray Positions	N/A
Poor Open Depth (mm)	905mm
Replacement Door Seal	No
pen Door Sensor	Yes
ock	Yes, 2 Keys
Adjustable Feet (number & position)	2 Adjustable (front)
Porthole	Yes
Porthole Size	16mm
Porthole Location	Rear Bottom (Right)
emperature Display on Panel	Yes
emperature Alarm	Yes
Remote Alarm Contacts	Yes
Audible Alarms	Yes
/isual Alarms	Yes
Number of Shelves/Drawers	1
Number of Shelf Positions	1
Shelf Size (mm) (WxDxH)	365mm X 190mm X 10.8mm
Shelf Material	Polythene Coated Wire
Number of Baskets	1 Olytheric coated Wife
Basket Material	Polythene Coated Wire
	363mm x 150mm x 152mm
Basket Size (mm) (WxDxH)	
nterior Light	No
an	No Vos
park Free	Yes
Defrost setting	Manual
Controller Type	Digital, External
Number of Probes	
Probe Type	Air
Ambient Temperature Range	10°C to 32°C
Refrigerant Type	R600a/40g
U. Z. Dim Dillim	Yes
	Yes
ther Plug Types Available	
Other Plug Types Available Yoltage Supply	220-240V
Other Plug Types Available Yoltage Supply	
Other Plug Types Available /oltage Supply irequency (Hz) Max Power (W)	220-240V
Other Plug Types Available /oltage Supply Frequency (Hz) Max Power (W) Max Current Rating (A)	220-240V 50Hz
Other Plug Types Available /oltage Supply Frequency (Hz) Max Power (W) Max Current Rating (A)	220-240V 50Hz 90W
Other Plug Types Available /oltage Supply Frequency (Hz) Max Power (W) Max Current Rating (A) Fnergy Consumption (kWh/24h)	220-240V 50Hz 90W 0.8A
Other Plug Types Available /oltage Supply Frequency (Hz) Max Power (W) Max Current Rating (A) Energy Consumption (kWh/24h) Energy Consumption AE (kWh)	220-240V 50Hz 90W 0.8A 1.40kWh/24hr
Other Plug Types Available /oltage Supply Frequency (Hz) Max Power (W) Max Current Rating (A) Finergy Consumption (kWh/24h) Finergy Consumption AE (kWh) Noise Level (dB)	220-240V 50Hz 90W 0.8A 1.40kWh/24hr 511.0kWh
Other Plug Types Available /oltage Supply Frequency (Hz) Max Power (W) Max Current Rating (A) Energy Consumption (kWh/24h) Energy Consumption AE (kWh) Noise Level (dB) Insulation Thickness (mm)	220-240V 50Hz 90W 0.8A 1.40kWh/24hr 511.0kWh 35.2dB 50mm
JK 3 Pin Plug Other Plug Types Available /oltage Supply Frequency (Hz) Max Power (W) Max Current Rating (A) Energy Consumption (kWh/24h) Energy Consumption AE (kWh) Noise Level (dB) Insulation Thickness (mm) Insulation Type Blowing Agent	220-240V 50Hz 90W 0.8A 1.40kWh/24hr 511.0kWh 35.2dB

